

Power system

DPS 4000B-48-6

Description

The DPS 4000B-48-6 is based on Delta DPR 4000B EnergE rectifiers. It belongs to the Delta CabD product series. This energy efficient, high power density system is ideal for space critical applications. An integrated modular system allows flexible and adaptable installations.

The system includes up to six rectifiers, AC and DC connections, battery connection and the Delta PSC 3 controller. In addition, easy installation and expandability add to the success of the system.

Delta is known for quality and product reliability, and to this solution has been added cost-effectiveness.

Main features

- DPR 4000B-48 EnergE rectifiers
 - Efficiency 95 %
 - Remarkable cost savings of cooling
- Up to 24 kW (in one cabinet)
- Power system controller PSC 3

Applications

- Core network components
- Telecommunications and data networks



Our product portfolio includes both indoor and outdoor power systems building on extensive R&D, modular production and customization. InD and OutD categories with CellD, MidD and CabD series can meet any of your size and location requirements.

CabD series can secure up to hundreds of kW of premium-quality electricity. The modularity and scalability of the systems enable fast roll-out and ease of expansion when needed. CabD offers the option of parallel installation for maximum capacity. The entire system can be controlled by a single unit.



Technical specifications

1. Input	
AC connection	(3L + N + PE)
Nominal voltage	3 x 230 V _{RMS} (L-N)
Voltage range	88 - 300 V _{RMS}
Frequency range	45 - 66 Hz
Current nominal	(3 x 46 A _{RMS}) @ 24kW
Mains terminal	Main switch (3~) Terminal block (3~)
Input protection, recom.	3 x 50 A (3~)
Transient OVP	Option

2. Output	
Voltage range	42 - 58 V _{DC} ; 53.5 V _{DC nom}
Power, nominal	24 kW
Two rows (See for distribution units)	DFU 40 x MCB DFU 30 x MCB DFU 20 x MCB DFU 14 x 00 DFU 6 x 00 + 18 x MCB
PLD	Option
Battery fuse	1 - 9 x MCB 80 A - 125 A 1 - 3 x MCB 160 A - 300A 1 - 6 x 00 63 A - 160 A 1 - 3 x 02 100 A - 400 A 1 - 2 x 03 315 A - 630 A
LVD	Option

Ordering information	
Product line number	3791199200
Description	DPS 4000B-48-6

3. General	
Height, overall	1800, 2000, 2200 mm
Width, body	600 mm
Depth, overall	600 mm
Weight, system	≤ 220 kg
Efficiency	95 %
Ambient temperature	-5 to +45 °C
Relative humidity	95 % max, non cond.
Safety	IEC/EN 60950
EMC	EN 300 386
Protection	IP 20
Controller	PSC 3
Rectifier	DPR 4000B-48

Subject to change without notice.



Delta Energy Systems (Finland) Oy
Juvan teollisuuskatu 15, FIN-02921 Espoo
Phone: +358 9 849 660, Fax: +358 9 8496 6100

www.deltapowersolutions.com